



- NOTES:
- 1) Wiring: type ET 24-19 MIL-W-16878, vinyl sleeving covered. harness lenght 0.3 mt min.
 - 2) "A" Joy EBR 316 actuation force:15 N
 - 3) "B" Toggle pushbutton actuation force: 8 N to 22.5 N
 - 4) "C" Slide actuation force:8 N
 - 5) "E" switch actuation force: 7.7 N ± 2.2 N
 - 6) "H" Pushbutton toggle switch actuation force:
Toggle switch : 11.3 ± 3.4 N
Pushbutton: 20.4 ±3.2 N
 - 7) Trigger switches actuation force:
- 1st detent: 6 to 12 N
- 2nd detent: 3 to 6 N over 1st detent actuating force.
(force applied horizontally about 8 mm above the lower tip of trigger switch actuator)
 - 8) Bar switch actuation force: 9 to 16 N.
(force applied horizontally about 8 mm above the lower tip of trigger switch actuator)
 - 9 Identification label: Manufacturer, P/N, S/N
 - 10) Further info on Dwg. HGJ 226 sheet 2 and sheet 3

NOTE: The EBR215 is equal the EBR316

REV.	DATE	DESCRIPTION	DRAWN	CONTROLLED	APPROVED
6	07/03/07	MOD. JOY P/N from EBR215 in to EBR316		LB	
5	31/03/04	ADDED OUT-PUT DIRECTION.		RBF	
4	30-03-04	UPDATING		RBF	
3	03/01/03	UPDATING		RBF	
2	28/11/02	FLANGE HG-00-78 ADDED		MB	
1	07/06/02	MOD. P/N POS. B-E-H		RBF	
0	29/05/02	FIRST EMISSION		RBF	

COSTUMER:			SUPPLY:		
LEGEND: HANDGRIP SPECIFICATION CONTROL DRAWING			CATEGORY:	MATERIAL:	WEIGHT:
			CRITICAL:	TREATMENT:	
			SPEC. TECN. N° :	SUPERSEDES:	SCALE: 1:2
			MODIFIES:		
		ACTION	DATA	NAME	COMPLEMENTARY DOCUMENTS:
<small>S.r.l. - Via 000000000 - 0 - MASSA - ITALY Phone : +39/0585/251818 Fax : +39/0585/251711 E - mail : people@so.ge.it</small>		DRAWN	29/05/2002	RBF	DWG. NUMBER: HGJ 226
		CONTROLLED			SHEET 1/3
		APPROVED			

This drawing is exclusive property of SO.GE.IN S.r.l. (MASSA, Italy) - Copy and transmission are prohibited by the terms of law